

PRODUCT SPECIFICATION

DATE : 05/14/2007

| | | | |
|---|---------------------------------|--------------|------|
| cosmo ELECTRONICS CORPORATION | Photocoupler : KP5010 | NO.60P21009 | REV. |
| | | SHEET 1 OF 6 | 3 |

High Reliability Photocoupler

● Features

1. High current transfer ratio ($V_{ce0} : 300V \text{ min}$)
(CTR : Min. 600% at $I_F=1mA$ $V_{CE}=2V$)
2. High isolation voltage between input and output
(Viso : 5000Vrms)
3. Compact dual-in-line package.

● Application :


1. System appliances, measuring instruments.
2. Industrial robots.
3. Copiers, automatic vending machines.
4. Signal transmission between circuits of different potentials and impedances.
5. Telephone sets.
6. Copiers, facsimiles.
7. Interface with various power supply circuits, power distribution boards.
8. Numerical control machines.

PRODUCT SPECIFICATION

DATE : 05/14/2007


| | | | |
|---|---------------------------------|--------------|-----------|
| cosmo ELECTRONICS CORPORATION | Photocoupler : KP5010 | NO.60P21009 | REV. 3 |
| | | SHEET 2 OF 6 | |

● Outside Dimension : Unit (mm)



TOLERANCE : ±0.2mm

● Schematic : Top View



1. Anode
2. Cathode
3. NC
4. Emitter
5. Collector
6. Base

PRODUCT SPECIFICATION

DATE : 05/14/2007

| | | | |
|---|---------------------------------|--------------|-----------|
| cosmo ELECTRONICS CORPORATION | Photocoupler : KP5010 | NO.60P21009 | REV. 3 |
| | | SHEET 3 OF 6 | |

● Absolute Maximum Ratings

| Parameter | | Symbol | Rating | Unit |
|---------------------------------|-----------------------------|-----------|-------------|------|
| Input | Forward current | I_F | 50 | mA |
| | Peak forward current | I_{FM} | 1 | A |
| | Reverse voltage | V_R | 6 | V |
| | Power dissipation | P_D | 70 | mW |
| Output | Collector-emitter voltage | V_{CEO} | 300 | V |
| | Collector-base voltage | V_{CBO} | 300 | V |
| | Emitter-base voltage | V_{EBO} | 6 | V |
| | Collector current | I_C | 150 | mA |
| | Collector power dissipation | P_C | 200 | mW |
| Total power dissipation | | P_{tot} | 200 | mW |
| Isolation voltage 1 minute | | V_{iso} | 5000 | Vrms |
| Operating temperature | | T_{opr} | -55 to +115 | °C |
| Storage temperature | | T_{stg} | -55 to +125 | °C |
| Soldering temperature 10 second | | T_{sol} | 260 | °C |

● Electro-optical Characteristics

| Parameter | | Symbol | Conditions | MIN. | TYP. | MAX. | Unit |
|--------------------------|------------------------------|---------------|--------------------------------------|--------------------|------|------|----------|
| Input | Forward voltage | V_F | $I_F=20mA$ | - | 1.2 | 1.4 | V |
| | Peak forward voltage | V_{FM} | $I_{FM}=0.5A$ | - | - | 3.5 | V |
| | Reverse current | I_R | $V_R=4V$ | - | - | 10 | μA |
| | Terminal capacitance | C_t | $V=0, f=1KHz$ | - | 30 | - | pF |
| Output | Collector dark current | I_{CEO} | $V_{CE}=200V$ | - | - | 1 | μA |
| Transfer characteristics | Current transfer ratio | CTR | $I_F=1mA, V_{CE}=2V$ | 600 | - | 9000 | % |
| | Collector-emitter saturation | $V_{CE(sat)}$ | $I_F=20mA, I_C=5mA$ | - | - | 1.5 | V |
| | Isolation resistance | R_{iso} | DC500V | 5×10^{10} | - | - | Ω |
| | Floating capacitance | C_f | $V=0, f=1MHz$ | - | 0.6 | 1.0 | pF |
| | Cut-off frequency | f_C | $V_{CC}=5V, I_C=2mA, R_L=100\Omega$ | - | 7 | - | KHz |
| | Response time (Rise) | t_r | $V_{CE}=2V, I_C=20mA, R_L=100\Omega$ | - | 60 | 300 | μs |
| | Response time (Fall) | t_f | | - | 50 | 250 | μs |

PRODUCT SPECIFICATION

DATE : 05/14/2007

| | | | | |
|---|----------------|---------------|--------------|------|
| cosmo ELECTRONICS CORPORATION | Photocoupler : | KP5010 | NO.60P21009 | REV. |
| | | | SHEET 4 OF 6 | 3 |

Classification table of current transfer ratio is shown below.

| Model No. | CTR (%) |
|-----------|-------------|
| KP50101A | 600 ~ 2000 |
| KP50101B | 1500 ~ 4000 |
| KP50101C | 3000 ~ 6000 |
| KP50101D | 5000 ~ 9000 |
| KP50101E | 600 ~ 9000 |

Fig.1 Current Transfer Ratio vs. Forward Current




Fig.2 Collector Power Dissipation vs. Ambient Temperature




Fig.3 Collector Dark Current vs. Ambient Temperature




Fig.4 Forward Current vs. Ambient Temperature





Fig.5 Forward Current vs. Forward Voltage



PRODUCT SPECIFICATION

DATE : 05/14/2007

| | | | |
|---|----------------|--------------|-----------|
| cosmo ELECTRONICS CORPORATION | Photocoupler : | NO.60P21009 | REV. 3 |
| | KP5010 | SHEET 5 OF 6 | |

Fig.6 Collector Current vs. Collector-Emitter Voltage




Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.8 Collector-Emitter Saturation Voltage vs. Forward Current





Fig.9 Response time vs. Load Resistance



PRODUCT SPECIFICATION

DATE : 05/14/2007

| | | | |
|---|---------------------------------|--------------|------|
| cosmo ELECTRONICS CORPORATION | Photocoupler : KP5010 | NO.60P21009 | REV. |
| | | SHEET 6 OF 6 | 3 |

● Notice

The information contained in this document is intended to be a general product description and is subject to change without notice. Please contact cosmo in order to obtain the latest device data sheets before using any cosmo device. cosmo does not assume any responsibility for use of any circuitry described. No circuit patent licenses are implied. This publication is the property of cosmo. No part of this publication may be reproduced or copied in any form or by any means, or transferred to any third party without the prior written consent of cosmo Electronics Corporation.

The devices listed in this document are designed for general applications only in electronic equipment. No devices shall be deployed which require higher level of reliability such as :

- Medical and other life support equipments.
- Space application.
- Telecommunication equipment (trunk lines).
- Nuclear power control equipment.

Unless it received prior written approval from cosmo.

cosmo takes no responsibility for damages arise form the improper usage of our device. Please contact cosmo for further information regarding the above notices.